

Uncontrolled When Printed

JOB NUMBER
34761

QMF 65

Road/Rail MEWP Braking Test

Machine Type Z60/34
 Serial No Z6008-8805
 Fleet No FR1330

Date 25/7/2011
 Next Test Due 25/7/2012
 NB: RRVs are 12 monthly

Perform All Tests

Test 1: SERVICE BRAKE TEST

Carry out on level track with the maximum trailing load behind the RRV as referenced in the Engineering Acceptance Certificate. Repeat at the same speed 3 or 4 times:

	Speed (kph)	Stopping Distance (m)
1	8	1.5
2	16	5.00
3		
4		

Trailing Load behind RRV (if applicable): N/A kg

What was the condition of the track? DRY LEVEL
 (Wet, dry, icy, gradient?, oil/grease?, cant etc.)

For guidance, the following maximum stopping distances should NOT be exceeded:

Speed (kph)	Stopping Distance (m)
8	6
16	18
24	36
32	60

Test 2: PARK BRAKE TEST

To be measured EITHER using a load cell on level track and noting the reading at the point when slippage occurs OR placing the machine on a track with a 1:29 gradient, the brakes should hold. If using a load cell then the following reading should be achieved.

RRV Type	Min Load	RRV Type	Min Load
CX135	550kg	12m Genie	340kg
988 Mega	817kg	20m Genie	604kg
988 Super	667kg	LH Skyboom	424kg
PC138	584kg	AR14	480kg
Gigarailer	1011kg	AR17	492kg
Mecalac 14	660kg		

FR3003
 Load Cell Reading: 750 kg

Result PASS FAIL

Test 3: RAIL AXLE BRAKE TEST

To be carried out exactly as above but with road wheels NOT in contact with either the ground or the rail wheels, track gradient or load cell readings as above.

Result PASS FAIL

Tested By:.....(Signature)

N. PUFFETT
(Print Name)

44-8